



Product Description

HPI-T High Wattage

Quartz metal halide lamps with clear outer bulb

Benefits

- High safety and comfort level, maintained over life
- Minimal maintenance cost

Features

- Clear tubular outer bulb
- Unique 3-band technology resulting in high luminous efficacy, both initially and over long lifetime
- Renders a natural white colour appearance and good colour stability

Application

- Sports lighting, floodlighting of buildings and monuments, area lighting e.g. harbours and building sites

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- For use with control gear designed for high-pressure mercury lamps
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

HPI-T High Wattage

Controls and Dimming

Dimmable	No
----------	----

Operating and Electrical

Voltage (Max)	140 V
Voltage (Min)	120 V
Voltage (Nom)	130 V

General Information

Cap-Base	E40
Life To 10% Failures (Nom)	5500 h
Life To 20% Failures (Nom)	8000 h
Life To 50% Failures (Nom)	12000 h
Life To 5% Failures (Nom)	3000 h
System Description	-

Light Technical

Colour Designation	Cool White (CW)
--------------------	-----------------

Mechanical and Housing

Bulb Finish	Clear
-------------	-------

Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/	Mercury (Hg) Content
		1000 h	(Nom)
928073609231	HPI-T 2000W/646 E40 220V CRP/4	2178 kWh	155 mg
928482600096	HPI-T 1000W/543 E40 1SL/4	1089 kWh	86 mg

Operating and Electrical

Order Code	Full Product Name	Lamp Current (EM)	
		(Nom)	Power (Nom)
928073609231	HPI-T 2000W/646 E40 220V CRP/4	16.5 A	1980 W

Order Code	Full Product Name	Lamp Current (EM)	
		(Nom)	Power (Nom)
928482600096	HPI-T 1000W/543 E40 1SL/4	8.25 A	990 W

General Information

Order Code	Full Product Name	Operating Position
928073609231	HPI-T 2000W/646 E40 220V CRP/4	P75

Order Code	Full Product Name	Operating Position
928482600096	HPI-T 1000W/543 E40 1SL/4	P

Luminaire Design Requirements

Order Code	Full Product Name	Bulb Temperature (Max)
928073609231	HPI-T 2000W/646 E40 220V CRP/4	600 °C

Order Code	Full Product Name	Bulb Temperature (Max)
928482600096	HPI-T 1000W/543 E40 1SL/4	555 °C

Light Technical (1/2)

Order Code	Full Product Name	Chromaticity	Chromaticity	Correlated Colour	
		Coordinate X (Nom)	Coordinate Y (Nom)	Code	Temperature (Nom)
928073609231	HPI-T 2000W/646	375	385	646	4200 K

Order Code	Full Product Name	Chromaticity	Chromaticity	Correlated Colour	
		Coordinate X (Nom)	Coordinate Y (Nom)	Code	Temperature (Nom)
928482600096	HPI-T 1000W/543 E40 1SL/4	370	380	543	4300 K

Light Technical (2/2)

HPI-T High Wattage

Order Code	Full Product Name	Colour	Lumen Maintenance 10000 h (Nom)	Lumen Maintenance 2000 h (Nom)	Lumen Maintenance 5000 h (Nom)	Luminous Efficacy (rated) (Nom)	Luminous Flux (Rated) (Min)	Luminous Flux (Rated) (Nom)
		Rendering Index (Nom)						
928073609231	HPI-T 2000W/646 E40 220V CRP/4	63	60 %	77 %	67 %	95 lm/W	182000 lm	189000 lm
928482600096	HPI-T 1000W/543 E40 1SL/4	57	75 %	87 %	80 %	83 lm/W	73890 lm	82100 lm

Mechanical and Housing

Order Code	Full Product Name	Bulb Shape	Order Code	Full Product Name	Bulb Shape
928073609231	HPI-T 2000W/646 E40 220V CRP/4	T100	928482600096	HPI-T 1000W/543 E40 1SL/4	T65

