



Tango G3 - BVP38x

BVP384 LED614/CW 490W 220-240V SWB GM

The energy-saving Philips Tango G3 LED Floodlight is the ideal solution for a wide range of Area lighting applications. It incorporates the LED light source, optical system, heat sink and driver into one compact and robust housing that meets globally recognised safety standards. Its specially designed heat sink incorporates aesthetics and functionality to ensure excellent reliability. Powered by LED technology, this luminaire delivers superior performance and a longer lifetime, bringing area lighting to a whole new level.

Product data

General Information		Optical cover/lens material		Polycarbonate
Lamp colour code	757 cool white	Colour	Aluminium and Grey	
Driver included	Yes	Approval and Application		
Optical cover/lens type	Polycarbonate micro lens optic	Ingress protection code	IP66 [Dust penetration-protected, jet-proof]	
Control interface	-	Mech. impact protection code	IK08 [5 J vandal-protected]	
Connection	Flying leads/cables	Initial Performance (IEC Compliant)		
Cable	Cable 0.5 m without plug	Initial luminous flux	61400 lm	
Protection class IEC	Safety class I	Luminous flux tolerance	+/-10%	
CE mark	CE mark	Initial LED luminaire efficacy	127 lm/W	
Operating and Electrical		Lamp colour temperature	5700 K	
Input Voltage	220 to 240 V	Colour Rendering Index	>70	
Input frequency	50 or 60 Hz	Initial input power	490 W	
Power factor (min.)	0.9	Power consumption tolerance	+/-10%	
Controls and Dimming		Application Conditions		
Dimmable	No	Ambient temperature range	-40 to +50 °C	
Mechanical and Housing				
Housing material	Aluminium die-cast			

Tango G3 - BVP38x


Product Data

Full product code	911401617706
Order product name	BVP384 LED614/CW 490W 220-240V SWB GM
Order code	911401617706
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1

SAP material	911401617706
Net Weight (Piece)	18.999 kg



Dimensional drawing



BVP38x Tango G3

