



GreenSpace Flex

RS378B P6 927 PSU-E MB M55

GreenSpace Flex, 6 W, 927 warm white, 24°, Finger-protected

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

Product data

General Information		Luminaire light beam spread	
Number of gear units	1 unit	Luminaire light beam spread	24°
Driver included	Yes	Operating and Electrical	
Light source engine type	LED	Input Voltage	220 to 240 V
CE mark	-	Line Frequency	50 or 60 Hz
Warranty period	3 years	Average CLO power consumption	365 W
Flammability mark	-	Power Consumption	6 W
ENEC mark	-	Power Factor (Fraction)	0.9
Glow-wire test	Temperature 600 °C, duration 30 s	Connection	External connector
EU RoHS compliant	Yes	Cable	-
Light Technical		Number of products on MCB of 16 A type B	-
Luminous Flux	450 lumen	Temperature	
Correlated Color Temperature (Nom)	2700 K	Ambient temperature range	-20 to +45 °C
Luminous Efficacy (rated) (Nom)	75 lm/W	Controls and Dimming	
Color rendering index (CRI)	<gt;/>90	Dimmable	No
Beam angle of light source	- degree(s)	Driver/power unit/transformer	Electronic transformer
Light source color	927 warm white	Control interface	-
Optic type	-	Constant light output	No
Optical cover/lens type	-		

Greenspace Flex

Mechanical and Housing

Housing Material	Aluminum Alloy
Reflector material	-
Optic material	Polymethyl methacrylate
Optical cover/lens material	-
Fixation material	Aluminum
Housing Color	Dark gray
Optical cover/lens finish	-
Overall length	0 mm
Overall width	0 mm
Overall height	49 mm
Overall diameter	55 mm
Dimensions (Height x Width x Depth)	49 x 0 x 0 mm

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK04 [0.5 J standard plus]
Protection class IEC	Safety class II

Initial Performance (IEC Compliant)

Initial chromaticity	SDCM<lt/>3
----------------------	------------

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Median useful life L80B50	50000 hour(s)
---------------------------	---------------



Application Conditions

Maximum dim level	Not applicable
Suitable for random switching	No

Product Data

Full product code	911401720922
Order product name	RS378B P6 927 PSU-E MB M55
Order code	911401720922
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	48
Material Nr. (12NC)	911401720922
Full product name	RS378B P6 927 PSU-E MB M55

Dimensional drawing



Modular Type	D, mm	H, mm
RS378B P6/P11 M55	55	49
RS378B P15 M55	55	49
RS378B P24 M70	70	90
RS378B P33 M87	87	107
RS378B P42 M102	102	116

