



GreenUp Lowbay G2

BY288P LED60/CW PSU EN

Cool white - Power supply unit

Good lighting is essential in industrial workspaces and large indoor areas. The wrong choice of lights or a lighting not correctly planned can lead to eye strain, fatigue, and poor performance, compromising safety and productivity. The Philips GreenUp Lowbay G2 luminaire is a simple LED solution which efficiently illuminates work areas, creating a brighter and better work, retail or sporting environment. With its crisp, white light and high colour rendering index coupled with energy efficiency, high visibility and enhances safety 24/7. Equipped with motion detection function, this easy-to-install and low-maintenance lighting solution is suitable for a variety of applications.

Product data

General Information		Operating and Electrical	
Lamp colour code	Cool white	CE mark	CE mark
Light source replaceable	No	ENEC mark	-
Number of gear units	1 unit	Warranty period	3 years
Driver/power unit/transformer	Power supply unit	Constant light output	No
Driver included	Yes	Number of products on MCB (16 A type B)	24
Optic type	-	EU RoHS compliant	No
Optical cover/lens type	Opal	Light source engine type	LED
Luminaire light beam spread	102°		
Control interface	-	Input Voltage	220-400 V
Connection	Flying leads/cables	Input frequency	50 or 60 Hz
Cable	Cable 0.3 m without plug	Inrush current	3.5 A
Protection class IEC	Safety class I	Inrush time	0.05 ms
Glow-wire test	Temperature 650 °C, duration 5 s	Power factor (min.)	0.95
Flammability mark	For mounting on normally flammable surfaces		

GreenUp Lowbay G2

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Housing material	Aluminium die-cast
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	-
Optical cover/lens finish	Frosted
Overall height	144 mm
Overall diameter	250 mm
Colour	Grey

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]

Initial Performance (IEC Compliant)

Initial luminous flux	5900 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	118 lm/W
Lamp colour temperature	6500 K
Colour Rendering Index	>80

Initial chromaticity	(0.313,0.324)SDCM<5
Initial input power	50 W
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Median useful life L70B50	50000 h
Median useful life L80B50	40000 h
Median useful life L90B50	20000 h

Application Conditions

Ambient temperature range	-20 to +45 °C
Suitable for random switching	No

Product Data

Full product code	911401843399
Order product name	BY288P LED60/CW PSU EN
Order code	911401843399
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1
SAP material	911401843399
Net Weight (Piece)	2.900 kg



Dimensional drawing



BY288P/BY288X GreenUp Lowbay G2

