



HID-Basic Semi-Parallel ballasts for SON/CDM/MH lamps

BSN 70L 300I TS

The HID Basic Semi-Parallel ballast is an impregnated (HID standard) electromagnetic copper/iron ballast for use with an external ignitor for HID lamps.

Product data

General Information	
Application code	L300 ITS
Operating and Electrical	
Input Voltage	220 V
Input frequency	50 Hz
Power factor 100% load (min.)	0.40
Mains voltage performance (AC)	-8% - +6%
Mains voltage safety (AC)	-10% - +10%
Input current with PF correction	0.98 A
Input current without PF Correction	0.98 A
Wiring	
Connector type	Screw
System characteristics	
Rated ballast-lamp power	70 W


Temperature	
T-winding (max.)	130 °C
Delta-T normal conditions	75 °C

Approval and Application	
Approval marks	CE marking CCC certificate

Product Data	
Full product code	697480505085700
Order product name	BSN 70L 300I TS
EAN/UPC – product	6974805050857
Order code	913710106942
SAP numerator – quantity per pack	1
Numerator – packs per outer box	6
SAP material	913710106942
SAP net weight (piece)	1.100 kg

HID-Basic Semi-Parallel ballasts for SON/CDM/MH lamps

Dimensional drawing



Product	D1	C1	A1	A2	B1
BSN 70L 300I TS	6.2 mm	51.5 mm	117.0 mm	110 mm	57.1 mm

BSN 70L 300I TS

