

# HID-Basic ballasts for HPL and HPI(PLUS) lamps

## BHLE 250L 202


The HID-Basic ballast is an impregnated (HID standard) electromagnetic ballast for HID lamps, for use in combination with an external ignitor.

### Product data

General Information		Temperature	
Application code	L202	T-winding (max.)	130 °C
		Delta-T normal conditions	70/75 °C
Operating and Electrical		Approval and Application	
Input Voltage	230 V	Approval marks	CE marking
Input frequency	50 Hz		
Power factor 100% load (min.)	0.85	Product Data	
Mains voltage performance (AC)	-8%~+6%	Full product code	872790084179400
Mains voltage safety (AC)	-10%~+10%	Order product name	BHLE 250L 202
Input current with PF correction	1.35 A	EAN/UPC – product	8711500997906
Input current without PF Correction	2.13/2.15 A	Order code	913713017550
Power factor without PF compensation (nom.)	0.60	SAP numerator – quantity per pack	1
Power losses (nom.)	21.6 W	Numerator – packs per outer box	6
		SAP material	913713017550
Wiring		SAP net weight (piece)	2.070 kg
Connector type	Screw		
System characteristics			
Rated ballast-lamp power	250 W		

## HID-Basic ballasts for HPL and HPI(PLUS) lamps

### Dimensional drawing



Product	D1	C1	A1	A2	B1
BHLE 250L 202	6.2 mm	64.5 mm	132.5 mm	119.0 mm	75.5 mm

BHLE 250L 202

