

HID-Basic Semi-Parallel Economic ballasts for SON/CDM/MH lamps

BSNE 70L 300I TS

Impregnated (HID standard) electromagnetic ballasts, of copper/iron construction, for use in combination with an external ignitor, for HID lamps

Product data

General Information	
Application code	L300 I
Design	TS
Operating and Electrical	
Input Voltage	220 V
Input frequency	50 Hz
Power factor 100% load (min.)	0.45
Mains voltage performance (AC)	-8%~+6%
Mains voltage safety (AC)	-10%~+10%
Input current with PF correction	2.40 A
Input current without PF Correction	4.45 A
Power factor without PF compensation (nom.)	0.85
Power losses (nom.)	31.8 W


Wiring	
Connector type	Screw
System characteristics	
Rated ballast-lamp power	70 W
Temperature	
T-winding (max.)	130 °C
Delta-T normal conditions	70 °C
Approval and Application	
Approval marks	CE marking CCC certificate
Product Data	
Full product code	871829112695900
Order product name	BSNE 70L 300I TS
EAN/UPC – product	8718291126959

HID-Basic Semi-Parallel Economic ballasts for SON/CDM/MH lamps

Order code	913713019150
SAP numerator – quantity per pack	1
Numerator – packs per outer box	6
SAP material	913713019150

SAP net weight (piece)	1.020 kg
------------------------	----------

Dimensional drawing



BSNE 70L 300I TS

Product	D1	C1	A1	A2	B1
BSNE 70L 300I TS	6.3 mm	82 mm	165.0 mm	144 mm	96.0 mm

