

HID-Basic Semi-Parallel ballasts for SON/CDM/MH lamps

BSNE 250L 300I TS


The HID Basic Semi-Parallel ballast is an impregnated (HID standard) electromagnetic copper/iron ballast for use with an external ignitor for HID lamps.

Product data

General Information		Temperature	
Application code	L300 ITS	T-winding (max.)	130 °C
		Delta-T normal conditions	70 °C
Operating and Electrical		Approval and Application	
Input Voltage	220 V	Approval marks	CE marking CCC certificate
Input frequency	50 Hz		
Power factor 100% load (min.)	0.45	Product Data	
Mains voltage performance (AC)	-8%+6%	Full product code	697480505035200
Mains voltage safety (AC)	-10%+10%	Order product name	BSNE 250L 300I TS
Input current with PF correction	1.4 A	EAN/UPC – product	6974805050352
Input current without PF Correction	3.0 A	Order code	913713019459
Power factor without PF compensation (nom.)	0.85	SAP numerator – quantity per pack	1
Power losses (nom.)	26.2 W	Numerator – packs per outer box	6
		SAP material	913713019459
Wiring		SAP net weight (piece)	2.900 kg
Connector type	Screw		
System characteristics			
Rated ballast-lamp power	250 W		

HID-Basic Semi-Parallel ballasts for SON/CDM/MH lamps

Dimensional drawing



Product	D1	C1	A1	A2	B1
BSNE 250L 300I TS	6.3 mm	64.5 mm	165.0 mm	144 mm	75.0 mm

BSNE 250 L300 ITS

