



# HID-Basic Semi-Parallel ballasts for SON/CDM/MH lamps

## BSNE 400L 300I TS


The HID Basic Semi-Parallel ballast is an impregnated (HID standard) electromagnetic copper/iron ballast for use with an external ignitor for HID lamps.

### Product data

General Information		Temperature	
Application code	L300 ITS	T-winding (max.)	130 °C
Design	-	Delta-T normal conditions	70 °C
Operating and Electrical		Approval and Application	
Input Voltage	220 V	Approval marks	CE marking CCC certificate
Input frequency	50 Hz	Product Data	
Power factor 100% load (min.)	0.45	Full product code	697480505037600
Mains voltage performance (AC)	-8%~+6%	Order product name	BSNE 400L 300I TS
Mains voltage safety (AC)	-10%~+10%	EAN/UPC – product	6974805050376
Input current with PF correction	2.4 A	Order code	913713019559
Input current without PF Correction	4.6 A	SAP numerator – quantity per pack	1
Power factor without PF compensation (nom.)	0.85	Numerator – packs per outer box	4
Power losses (nom.)	31.8 W	SAP material	913713019559
Wiring		SAP net weight (piece)	4.500 kg
Connector type	Screw		
System characteristics			
Rated ballast-lamp power	400 W		

## HID-Basic Semi-Parallel ballasts for SON/CDM/MH lamps

### Dimensional drawing



BSNE 400L 300I TS

Product	D1	C1	A1	A2	B1
BSNE 400L 300I TS	6.3 mm	82 mm	165.0 mm	144 mm	96.0 mm

