



HF-Performer III for TL-D lamps

HF-P 118/136 TL-D III 220-240V 50/60 Hz

HF-Performer III TLD is a sustainable, slim and high-frequency electronic ballast for TL-D fluorescent lamps. It is ideal for applications where high energy efficiency is required. The HF-Performer III range has a robust design, meets all relevant international safety and performance standards and is energy-efficient (CELMA EEI A2).

Product data

General Information		Temperature	
Number of Lamps	1 piece/unit	Ambient temperature range	-25 °C to 60 °C
Operating and Electrical		T-Case Lifetime (Nom)	80 °C
Input Voltage	220 to 240 V	T-Case Maximum (Max)	80 °C
Line Frequency	50 to 60 Hz	Mechanical and Housing	
Input Frequency	50 to 60 Hz	Housing	L 280x30x28
Inrush Current Width	0.25 ms	Approval and Application	
Inrush Current Peak (Max)	18 A	Ingress protection code	IP20 [Finger-protected]
Number of Products on MCB (16A Type B) (Nom)	28	Energy Efficiency Index	A2 BAT
Wiring		Safety Standard	IEC 61347-2-3
Connector Type Input Terminals	WAGO 251 universal connector [Suitable for both automatic wiring (ALF and ADS) and manual wiring]	Environmental Standard	ISO 14001
Connector Type Output Terminals	WAGO 251 universal connector [Suitable for both automatic wiring (ALF and ADS) and manual wiring]	Approval Marks	CE marking ENEC certificate VDE-EMV certificate
		Product Data	
		Full product code	872790091164000
		Order product name	HF-P 118/136 TL-D III 220-240V 50/60 Hz
		Order code	913713031566

HF-Performer III for TL-D lamps

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material number (12NC)	913713031566
Full product name	HF-P 118/136 TL-D III 220-240V 50/60 Hz

EAN/UPC - Case	8727900911640
----------------	---------------



Dimensional drawing

A2

Product	D1	C1	A1	A2	B1
HF-P 118/136 TL-D III 220-240V 50/60 Hz	4.2 mm	28.0 mm	280.0 mm	265.0 mm	30.0 mm

