



GreenPerform Highbay Rectangular

BY570P LED250/CW PSD WB GM

- Transparent dome

The GreenPerform Highbay Rectangular continues the GreenPerform family's enviable reputation for reliable performance, provi. Not only does it deliver Unified Glare Rating (UGR) control with its optimized optical design, it also promises leading system efficiency, compact dimensions and extended long-term quality. Optimized for almost all industrial applications, it is also fully compatible with IoT software such as the Interact scalable system.

Product data

General Information		Power Factor (Fraction)		0.95
Light source engine type	LED	Number of products on MCB of 16 A type B		6
Light Technical		Temperature		
Luminous Flux	25,000 lumen	Ambient temperature range	-30 to +45 °C	
Correlated Color Temperature (Nom)	6500 K	Controls and Dimming		
Luminous Efficacy (rated) (Nom)	128 lm/W	Dimmable	Yes	
Color rendering index (CRI)	>80	Control interface	DALI	
Light source color	865 cool daylight	Mechanical and Housing		
Optical cover/lens type	Transparent dome	Housing Material	Aluminum die cast	
Operating and Electrical		Optical cover/lens material	Polycarbonate	
Input Voltage	220 to 240 V	Housing Color	Gray	
Line Frequency	50 or 60 Hz	Optical cover/lens finish	Clear	
Input Frequency	50 or 60 Hz	Overall length	32 mm	
Power Consumption	199 W			

GreenPerform Highbay Rectangular

Overall width	13 mm
Overall height	32.8 mm
Dimensions (Height x Width x Depth)	33 x 13 x 32 mm

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Protection class IEC	Safety class I
CE mark	CE mark

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Product Data

Full product code	911401593761
Order product name	BY570P LED250/CW PSD WB GM
Order code	911401593761
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2
Material number (12NC)	911401593761
Full product name	BY570P LED250/CW PSD WB GM



Dimensional drawing

