



# SportsStar- BVP621/BVP622/ EVP622

## BVP622 LED922/857 900W S3 GM 5C O

92200 lm - 900 W - 5700 K

Philips SportsStar LED Floodlight sets the standard in high quality optical distribution with high performance and low light pollution (or effective light control). From Sports to Area Lighting, our system, including the high masts needed, projects the light exactly where it should be going. Choose the right illumination levels for any given setting with Philips SportsStar LED Floodlight.

### Product data

General Information			
Lamp colour code	857 daylight	control units, surge-protection device, front cover and mechanical parts	
Light source replaceable	No		
Driver included	No		
Optical cover/lens type	Polycarbonate micro lens optic		
Control interface	-		
Connection	Connection unit 5-pole		
Cable	Cable 1.5 m with plug		
Protection class IEC	Safety class I		
Flammability mark	-		
CE mark	CE mark		
Light source engine type	LED		
Serviceability class	Class B, the luminaire is equipped with some serviceable parts (when applicable): driver,		
		Light Technical	
		Standard tilt angle post-top	-
		Standard tilt angle side entry	-
		Operating and Electrical	
		Input Voltage	- V
		Input frequency	- Hz
		Power factor (min.)	0.9

# SportsStar-BVP621/BVP622/EVP622

## Controls and Dimming

Dimmable	No
----------	----

## Mechanical and Housing

Housing material	Aluminium
Optical cover/lens material	Polycarbonate
Mounting device	Mounting bracket adjustable
Optical cover/lens finish	Frosted
Overall length	680 mm
Overall width	730 mm
Overall height	307 mm
Colour	White

## Approval and Application

Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [ 5 J vandal-protected]
Surge protection (common/differential)	-

## Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	92200 lm
Luminous flux tolerance	+/-10%


Initial LED luminaire efficacy	102.44 lm/W
Lamp colour temperature	5700 K
Colour Rendering Index	>80
Initial input power	900 W
Power consumption tolerance	+/-10%

## Application Conditions


Ambient temperature range	-40 to +50 °C
---------------------------	---------------

## Product Data

Full product code	911401596151
Order product name	BVP622 LED922/857 900W S3 GM 5C O
Order code	911401596151
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1
SAP material	911401596151
SAP net weight (piece)	21.999 kg



## Dimensional drawing



BVP622 LED922/857 900W S3 GM 5C O

