



Tango G3 - BVP38x

BVP384 LED504/857 480W DMX AWB GM

50400 lm - 480 W - 5700 K

The energy-saving Philips Tango G3 LED Floodlight is the ideal solution for a wide range of Area lighting applications. It incorporates the LED light source, optical system, heat sink and driver into one compact and robust housing that meets globally recognised safety standards. Its specially designed heat sink incorporates aesthetics and functionality to ensure excellent reliability. Powered by LED technology, this luminaire delivers superior performance and a longer lifetime, bringing area lighting to a whole new level.

Product data

General Information		Mechanical and Housing	
Lamp colour code	857 daylight	Housing material	Aluminium die-cast
Driver included	No	Optical cover/lens material	Polycarbonate
Optical cover/lens type	Polycarbonate micro lens optic	Colour	Aluminium and Grey
Control interface	Dynamix DMX	Approval and Application	
Connection	Flying leads/cables	Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Cable	Cable 0.5 m without plug	Mech. impact protection code	IK08 [5 J vandal-protected]
Protection class IEC	Safety class I	Initial Performance (IEC Compliant)	
CE mark	CE mark	Initial luminous flux (system flux)	50400 lm
Operating and Electrical		Luminous flux tolerance	+/-10%
Input Voltage	- V	Initial LED luminaire efficacy	109 lm/W
Input frequency	- Hz	Lamp colour temperature	5700 K
Power factor (min.)	0.9	Colour Rendering Index	>80
Controls and Dimming		Initial input power	480 W
Dimmable	Yes	Power consumption tolerance	+/-10%

Tango G3 - BVP38x

Application Conditions

Ambient temperature range -40 to +50 °C


Product Data

Full product code 911401619806
Order product name BVP384 LED504/857 480W DMX AWB GM
Order code 911401619806

SAP numerator – quantity per pack 1
Numerator – packs per outer box 1
SAP material 911401619806
SAP net weight (piece) 15.999 kg



Dimensional drawing



BVP38x Tango G3

