



GreenPerform Direct LED Panel

RC099V G2 LED36/865 PSU W30L120 OC

Polystyrene bowl/cover prismatic

The GreenPerform RC099V G2 direct panel is an affordable LED panel delivering comfortable light with excellent uniformity. It offers 3 types, 600 x 600, 300 x 1,200, and 600 x 1,200 mm with max: 110 lm/w system efficacy. Its UGR19 version brings more visual comfort in the office. By means of its compact design, the housing height (without driver) reaches only 35 mm which gives more flexibility for recessed installation.

Product data

General Information		Controls and Dimming	
Lamp colour code	865 cool daylight	Dimmable	No
Optical cover/lens type	Polystyrene bowl/cover prismatic		
Control interface	-	Mechanical and Housing	
Protection class IEC	Safety class II	Housing material	Steel
CE mark	CE mark	Optical cover/lens material	Polystyrene
Number of products on MCB (16 A type B)	24	Optical cover/lens finish	Opal
Light source engine type	LED	Overall length	1195 mm
		Overall width	295 mm
		Overall height	57 mm
Operating and Electrical		Colour	White RAL 9003
Input Voltage	220 to 240 V		
Input frequency	50 or 60 Hz	Approval and Application	
Power factor (min.)	0.9	Ingress protection code	IP20 [Finger-protected]
		Mech. impact protection code	-

GreenPerform Direct LED Panel

Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	3600 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	100 lm/W
Lamp colour temperature	6500 K
Colour Rendering Index	>80
Initial input power	35 W
Power consumption tolerance	+/-10%

Application Conditions


Ambient temperature range	-20 to +40 °C
---------------------------	---------------

Product Data

Full product code	692382864369099
Order product name	RC099V G2 LED36/865 PSU W30L120 OC
EAN/UPC – product	6923828643690
Order code	911401700873
SAP numerator – quantity per pack	1
Numerator – packs per outer box	4
SAP material	911401700873
SAP net weight (piece)	2.300 kg



Dimensional drawing



SmartBright Panel RC099V

