



# UniFlood C

## BVP321 9LED 40K 220V 45 DMX D2

UniFlood C is a circular shaped, exterior-rated and cost-effective architectural LED floodlight that is designed for façade, landscape and outdoor flood lighting applications. The robust mechanical design and high-efficiency optical design make it ideal for illuminating multi-story exterior facades, bridges, landmarks and monuments. Available in white, monochromatic colors, RGB, RGBW and tunable white. Six different spread lenses ranging from narrow spot to wide flood and DMX512/RDM control option available to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

### Warnings and Safety

- For outdoor use only

### Product data

General Information		Inrush current	
Driver included	Yes		60 A
Lighting Technology	LED	Power Consumption	21 W
Light Technical		Power Factor (Fraction)	0.9
Luminous Flux	1,720 lumen	Connection	Flying leads/wires and 2 Push-in connector 4-pole
Correlated Color Temperature (Nom)	-	Cable	Cable 0.5 m without plug 3-pole and 2 Cables 0.5 m with connector 4-pole
Luminous Efficacy (rated) (Nom)	82 lm/W	Temperature	
Color rendering index (CRI)	80	Ambient temperature range	-40 to +50 °C
Light source color	Neutral white	Controls and Dimming	
Optical cover/lens type	Tempered glass	Dimmable	Yes
Operating and Electrical		Control interface	Dynamic DMX/RDM
Input Voltage	220 to 240 V		
Line Frequency	50 to 60 Hz		
Input Frequency	50 to 60 Hz		

# UniFlood C

## Mechanical and Housing

Housing Material	Aluminum die cast
Optical cover/lens material	Polymethyl methacrylate
Housing Color	Dark gray
Effective projected area	0.03 m <sup>2</sup>

## Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Protection class IEC	Safety class I
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark

## Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
-------------------------	--------

Initial chromaticity	4 SDCM
Power consumption tolerance	+/-10%

## Product Data

Full product code	871951453802399
Order product name	BVP321 9LED 40K 220V 45 DMX D2
Order code	911401730353
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material number (12NC)	911401730353
Full product name	BVP321 9LED 40K 220V 45 DMX D2
EAN/UPC - Case	8719514538023



## Dimensional drawing

