



Essential SmartBright G3 LED Floodlight

BVP150 LED170/WW 220-240V 200W SWB CE

The Essential SmartBright G3 LED floodlight comes with a compact and sturdy design. Its light weight with robust die-cast aluminium housing and corrosion-proof coating is suitable for general outdoor use. More efficient than the last generation, achieves more energy-savings.

Product data

General Information	
Lamp colour code	830 warm white
Driver included	Yes
Optical cover/lens type	-
Control interface	-
Connection	Flying leads/cables
Cable	Cable 0.6 m without plug
Protection class IEC	Safety class I
CE mark	CE mark

Operating and Electrical	
Input Voltage	220 to 240 V
Input frequency	50 or 60 Hz
Power factor (min.)	0.9

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Housing material	Aluminium die-cast

Optical cover/lens material	Glass
Overall length	395 mm
Overall width	60 mm
Overall height	370 mm
Colour	Black

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]

Initial Performance (IEC Compliant)

Initial luminous flux	16000 lm
Luminous flux tolerance	+/-15%
Initial LED luminaire efficacy	80 lm/W
Lamp colour temperature	3000 K
Colour Rendering Index	>80
Initial input power	200 W
Power consumption tolerance	+/-15%

Essential SmartBright G3 LED Floodlight


Application Conditions

Ambient temperature range -40 to +50 °C


Product Data

Full product code 871016333032799
Order product name BVP150 LED170/WW 220-240V 200W SWB CE
EAN/UPC – product 8710163330327
Order code 911401732532

Numerator – quantity per pack 1
SAP numerator – packs per outer box 2
Material no. (12 NC) 911401732532
SAP net weight (piece) 4.540 kg



Dimensional drawing



BVP150/161 Essential Smartbright LED

