



UniStrip G4

BCP383 12LED 40K 220V 45 L50 D2

UniStrip G4, 2440 lumen, 27 W, 4000 K

UniStrip G4 is a surface mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications. One family that fits all your needs, wall washing, grazing and also linear flood lighting. The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution. Available in white, monochromatic colors, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

- For outdoor use only

Product data

| General Information | |
|------------------------------------|----------------|
| Driver included | Yes |
| Lighting Technology | LED |
| Light Technical | |
| Luminous Flux | 2,440 lumen |
| Correlated Color Temperature (Nom) | 4000 K |
| Luminous Efficacy (rated) (Nom) | 90 lm/W |
| Color rendering index (CRI) | 80 |
| Light source color | Neutral white |
| Optical cover/lens type | Tempered glass |
| Operating and Electrical | |
| Input Voltage | 220 to 240 V |

| Line Frequency | 50 to 60 Hz |
|---------------------------|---------------------------------|
| Inrush current | 60 A |
| Power Consumption | 27 W |
| Power Factor (Fraction) | 0.9 |
| Connection | Flying leads/wires |
| Cable | Cable 0.3 m without plug 3-pole |
| Temperature | |
| Ambient temperature range | -40 to +50 °C |
| Controls and Dimming | |
| Dimmable | No |
| Control interface | - |

UniStrip G4

Mechanical and Housing

| | |
|-----------------------------|-------------------------|
| Housing Material | Aluminum extruded |
| Optical cover/lens material | Polymethyl methacrylate |
| Housing Color | Dark gray |
| Effective projected area | 0.073 m ² |

Approval and Application

| | |
|------------------------------|--|
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK06 [1 J] |
| Protection class IEC | Safety class I |
| Flammability mark | For mounting on normally flammable surfaces |
| CE mark | CE mark |

Initial Performance (IEC Compliant)

| | |
|-------------------------|--------|
| Luminous flux tolerance | +/-10% |
|-------------------------|--------|

| | |
|-----------------------------|----------|
| Initial chromaticity | SDCM = 4 |
| Power consumption tolerance | +/-10% |

Product Data

| | |
|---------------------------------|---------------------------------|
| Full product code | 871951492168999 |
| Order product name | BCP383 12LED 40K 220V 45 L50 D2 |
| Order code | 911401736093 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 6 |
| Material Nr. (12NC) | 911401736093 |
| Full product name | BCP383 12LED 40K 220V 45 L50 D2 |
| EAN/UPC - Case | 8719514921689 |

Dimensional drawing

