



UniStrip G4

BCP383 18LED RGB 220V 45 L50 DMX D2

UniStrip G4, 1337 lumen, 27 W

UniStrip G4 is a surface mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications. One family that fits all your needs, wall washing, grazing and also linear flood lighting. The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution. Available in white, monochromatic colors, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

- For outdoor use only

Product data

| General Information | | Line Frequency | |
|------------------------------------|---------------------|---------------------------|--|
| Driver included | Yes | Line Frequency | 50 to 60 Hz |
| Lighting Technology | LED | Inrush current | 60 A |
| Light Technical | | Power Consumption | 27 W |
| Luminous Flux | 1,410 lumen | Power Factor (Fraction) | 0.9 |
| Correlated Color Temperature (Nom) | - | Connection | Flying leads/wires and 2 Push-in connector 4-pole |
| Luminous Efficacy (rated) (Nom) | 52 lm/W | Cable | Cable 0.3 m without plug 3-pole + 2 Cables 0.3 m with connector 4-pole |
| Color rendering index (CRI) | - | Temperature | |
| Light source color | Red, green and blue | Ambient temperature range | -40 to +50 °C |
| Optical cover/lens type | Tempered glass | Controls and Dimming | |
| Operating and Electrical | | Dimmable | Yes |
| Input Voltage | 220 to 240 V | | |

UniStrip G4

| | |
|---------------------------------|--|
| Control interface | Dynamic DMX |
| Mechanical and Housing | |
| Housing Material | Aluminum extruded |
| Optical cover/lens material | Polymethyl methacrylate |
| Housing Color | Dark gray |
| Effective projected area | 0.073 m ² |
| Approval and Application | |
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK06 [1 J] |
| Protection class IEC | Safety class I |
| Flammability mark | For mounting on normally flammable surfaces |
| CE mark | CE mark |

| | |
|--|-------------------------------------|
| Initial Performance (IEC Compliant) | |
| Luminous flux tolerance | +/-10% |
| Power consumption tolerance | +/-10% |
| Product Data | |
| Full product code | 871951492171999 |
| Order product name | BCP383 18LED RGB 220V 45 L50 DMX D2 |
| Order code | 911401736123 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 6 |
| Material Nr. (12NC) | 911401736123 |
| Full product name | BCP383 18LED RGB 220V 45 L50 DMX D2 |
| EAN/UPC - Case | 8719514921719 |

Dimensional drawing

