



UniStrip G4

BCP385 30LED RGB 220V A1 L52 DMX D3

UniStrip G4, 2545 lumen, 60 W

UniStrip G4 is a surface mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications. One family that fits all your needs, wall washing, grazing and also linear flood lighting. The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution. Available in white, monochromatic colors, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

- For outdoor use only

Product data

General Information		Line Frequency	
Driver included	Yes	Line Frequency	50 to 60 Hz
Lighting Technology	LED	Inrush current	60 A
Light Technical		Power Consumption	60 W
Luminous Flux	1,980 lumen	Power Factor (Fraction)	0.9
Correlated Color Temperature (Nom)	-	Connection	Flying leads/wires and 2 Push-in connector 4-pole
Luminous Efficacy (rated) (Nom)	33 lm/W	Cable	Cable 0.3 m without plug 3-pole + 2 Cables 0.3 m with connector 4-pole
Color rendering index (CRI)	-	Temperature	
Light source color	Red, green and blue	Ambient temperature range	-40 to +50 °C
Optical cover/lens type	Tempered glass	Controls and Dimming	
Operating and Electrical		Dimmable	Yes
Input Voltage	220 to 240 V		

UniStrip G4

Control interface	Dynamic DMX
Mechanical and Housing	
Housing Material	Aluminum extruded
Optical cover/lens material	Polymethyl methacrylate
Housing Color	Dark gray
Effective projected area	0.135 m ²
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Protection class IEC	Safety class I
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Product Data	
Full product code	871951492219899
Order product name	BCP385 30LED RGB 220V A1 L52 DMX D3
Order code	911401736763
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2
Material Nr. (12NC)	911401736763
Full product name	BCP385 30LED RGB 220V A1 L52 DMX D3
EAN/UPC - Case	8719514922198

Dimensional drawing

